

		平成23年度(2011)				平成24年度(2012)				平成25年度(2013)				平成26年度(2014)				
採取年月日		2011/5/27	2011/8/18	2011/11/22	2012/2/21	2012/5/14	2012/8/27	2012/11/7	2013/2/18	2013/5/28	2013/8/26	2013/11/12	2014/2/24	2014/5/22	2014/8/25	2014/11/25	2015/2/23	
証明年月日		2011/5/30	2011/9/1	2011/12/6	2012/3/6	2012/5/28	2012/9/10	2012/11/21	2013/3/4	2013/6/10	2013/9/9	2013/11/25	2014/3/7	2014/6/4	2014/9/8	2014/12/8	2015/3/6	
天候		晴	晴	晴	曇	曇	晴	晴	雨	雨	晴	雨	晴	晴	晴	雨	曇	
気温		単位 ℃	23.0	29.6	5.3	1.8	21.5	33.7	8.9	4.2	19.2	28.5	6.8	7.8	24.0	29.2	11.0	7.6
ごみの種類組成	紙、布類	%	72.2	64.1	59.7	68.3	57.3	64.6	60.3	62.6	63.2	61.2	60.1	51.5	62.9	55.8	55.2	63.2
	ビニール、皮革、ゴム、合成樹脂	〃	11.7	16.7	15.5	17.2	22.3	22.0	18.9	16.5	13.9	21.2	20.3	18.0	23.4	26.0	25.4	11.1
	木、竹、わら類	〃	2.2	1.9	2.7	3.3	11.4	0.8	5.7	0.6	5.7	3.5	3.7	1.6	7.4	1.7	10.7	0.5
	ちゅう芥類	〃	9.0	8.0	15.5	6.9	7.1	9.7	5.8	13.9	13.2	7.6	10.8	25.2	5.2	6.4	5.3	14.6
	不燃物類	〃	0.9	4.2	0.8	0.1	0.7	0.7	4.1	2.3	1.2	<0.1	1.4	1.1	0.2	1.9	0.5	8.2
三ごみ成分	水分	%	45.0	51.9	54.9	38.6	38.5	48.1	59.4	51.3	45.2	44.8	43.7	40.1	39.0	43.4	47.1	44.6
	灰分	〃	6.9	5.4	6.0	4.7	7.1	5.3	5.6	5.1	4.6	4.8	6.1	8.4	4.7	9.3	3.3	8.9
低位発熱量	可燃分	〃	48.1	42.7	39.1	56.7	54.4	46.6	35.0	43.6	50.2	50.4	50.2	51.5	56.3	47.3	49.6	46.5
	低位発熱量(計算値)	kJ/kg	7,930	6,740	5,990	9,710	9,280	7,570	5,100	6,920	8,320	8,370	8,360	8,690	9,620	7,820	8,160	7,640
低位発熱量(実測値)	〃	7,920	7,100	6,440	9,730	9,810	8,170	5,640	8,040	9,150	9,560	9,630	9,260	8,740	7,540	9,540	6,560	
		【平均】				【平均】				【平均】				【平均】				
ごみの種類組成	紙、布類	%	66.1				61.2				59.0				59.3			
	ビニール、皮革、ゴム、合成樹脂	〃	15.3				19.9				18.4				21.5			
	木、竹、わら類	〃	2.5				4.6				3.6				5.1			
	ちゅう芥類	〃	9.9				9.1				14.2				7.9			
	不燃物類	〃	1.5				2.0				1.2				2.7			
三ごみ成分	水分	%	45.0				38.5				45.2				39.0			
	灰分	〃	6.9				7.1				4.6				4.7			
低位発熱量	可燃分	〃	48.1				54.4				50.2				56.3			
	低位発熱量(計算値)	kJ/kg	7,593				7,218				8,435				8,310			
低位発熱量(実測値)	〃	7,798				7,915				9,400				8,095				
摘 要		※布、軟ブラの分別収集を本格実施。																
		※生ごみの堆肥化実験(最終年度)																

		平成27年度(2015)						平成28年度(2016)						平成29年度(2017)									
採取年月日		2015/5/25	2015/7/24	2015/9/24	2015/11/24	2016/1/22	2016/3/4	2016/5/23	2016/7/22	2016/9/26	2016/11/30	2017/1/27	2017/3/3	2017/5/29	2017/7/25	2017/9/25	2017/11/27	2018/2/2	2018/3/2				
証明年月日		2015/6/5	2015/8/6	2015/10/7	2015/12/7	2016/2/4	28.3.17	2016/6/3	2016/8/4	2016/10/7	2016/12/13	2017/2/9	2017/3/16	2017/6/9	2017/8/7	2017/10/6	2017/12/8	2018/2/15	2018/3/15				
天候		晴	晴	雨	雨	雨	曇	晴	晴	曇	曇	曇	曇	晴	曇	晴	曇	晴	晴				
気温		単位	℃	24.8	24.6	18.3	11.0	1.7	9.0	24.3	28.2	24.8	9.0	5.0	7.2	24.8	27.2	21.3	11.0	4.8	6.5		
ごみの種類組成	紙類	%	51.1	47.5	47.6	48.7	44.0	54.6	37.5	42.1	50.0	35.6	42.7	48.7	41.6	52.7	49.5	38.2	48.0	48.5			
	布類	〃	7.7	13.7	5.9	14.8	3.7	5.6	9.1	11.3	5.8	5.5	5.1	6.2	6.3	5.8	6.7	7.3	7.8	2.5			
	紙おむつ類	〃	4.1	10.2	11.8	3.4	7.3	4.7	6.0	3.2	9.9	8.8	18.7	5.0	8.8	10.0	5.1	22.5	11.2	2.6			
	ビニール、皮革、ゴム、合成樹脂	〃	21.1	12.9	19.9	15.6	21.4	17.3	16.9	27.1	16.2	25.1	13.8	21.8	17.4	19.9	23.3	16.5	13.7	24.7			
	木、竹、わら類	〃	6.9	5.9	1.1	2.1	0.8	3.0	4.5	3.6	5.8	2.2	1.0	0.4	10.4	3.7	2.6	1.4	0.6	4.8			
三ごみ成分	ちゅう芥類	〃	4.9	6.7	10.3	9.5	14.3	11.6	20.1	9.7	6.1	19.7	14.7	17.6	4.8	5.9	10.0	11.2	15.8	6.8			
	不燃物類	〃	0.7	<0.1	0.4	4.1	6.0	2.0	4.1	0.1	3.1	1.4	3.1	0.3	1.3	0.2	2.8	2.9	2.9	0.2			
低位発熱量	その他	〃	3.5	3.1	3.0	1.8	2.5	1.2	1.8	2.9	3.1	1.7	0.9	<0.1	9.4	1.8	0.0	0.0	0.0	9.9			
	単位容積重量	kg/m3	140	150	190	120	130	160	140	130	170	110	130	140	120	110	180	150	130	110			
三ごみ成分	水分	%	40.9	49.8	53.5	48.3	50.3	44.5	50.5	43.5	48.1	48.6	51.5	48.0	43.7	36.0	47.0	40.5	41.4	29.5			
	灰分	〃	3.9	6.0	4.1	5.4	7.3	7.6	5.9	4.7	8.8	5.0	7.6	3.8	6.6	4.4	4.9	9.9	3.8	10.5			
低位発熱量	可燃分	〃	55.2	44.2	42.4	46.3	42.4	47.9	43.6	51.8	43.1	46.4	40.9	48.2	49.7	59.6	48.1	49.6	54.8	60.0			
	低位発熱量(計算値)	kJ/kg	9,370	7,070	6,640	7,510	6,720	7,900	6,950	8,670	6,910	7,520	6,410	7,870	8,260	10,300	7,880	8,330	9,280	10,600			
低位発熱量	(実測値)	〃	9,500	7,710	6,480	9,090	8,940	8,610	9,160	10,500	7,140	9,040	7,860	9,070	8,530	11,800	9,690	10,400	10,400	13,200			
		【平均】						【平均】						【平均】									
ごみの種類組成	紙類	%	48.9							42.8							46.4						
	布類	〃	8.6							7.2							6.1						
	紙おむつ類	〃	6.9							8.6							10.0						
	ビニール、皮革、ゴム、合成樹脂	〃	18.0							20.2							19.3						
	木、竹、わら類	〃	3.3							2.9							3.9						
三ごみ成分	ちゅう芥類	〃	9.6							14.7							9.1						
	不燃物類	〃	2.6							2.0							1.7						
低位発熱量	その他	〃	2.5							2.1							3.5						
	単位容積重量	kg/m3	148							137							133						
三ごみ成分	水分	%	47.9							48.4							39.7						
	灰分	〃	5.7							6.0							6.7						
低位発熱量	可燃分	〃	46.4							45.7							53.6						
	低位発熱量(計算値)	kJ/kg	7,535							7,388							9,108						
低位発熱量	(実測値)	〃	8,388							8,795							10,670						
摘 要																							

(日南町環境エネルギー課)																														
			平成30年度(2018)				令和元年度(2019)				令和2年度(2020)				令和3年度(2021)				令和4年度(2022)				令和5年度(2023)							
採取年月日			2018/5/25	2018/8/27	2018/11/26	2019/2/27	2019/5/27	2019/8/26	2019/11/27	2020/2/28	2020/5/26	2020/8/24	2020/11/26	2021/2/26	2021/5/17	2021/8/24	2021/11/12	2022/2/28	2022/8/8	2022/11/22	2023/2/27		2023/5/29	2023/8/23	2023/11/15	2024/2/20				
証明年月日			2018/6/7	2018/9/10	2018/12/7	2019/3/12	2019/6/10	2019/9/6	2019/12/10	2020/3/12	2020/6/8	2020/9/4	2020/12/9	2021/3/11	2021/5/28	2021/9/4	2021/11/25	2022/3/11	2022/8/31	2022/12/7	2023/3/23		2023/7/3	2023/9/15	2023/12/11	2024/3/15				
天候			晴	晴	晴	曇	曇	晴	曇	曇	雨	晴	曇	雨	雨	晴	雨	曇	晴	曇	晴		雨	曇	晴	雨				
気温			単位	°C	25.9	29.1	8.4	6.4	24.0	26.5	9.0	7.0	23.8	32.0	13.6	1.3	24.3	28.0	7.0	10.0	28.1	12.0	5.7		22.0	26.8	8.1	9.8		
ごみの種類組	紙類、布類	%	65.3	55.1	59.0	66.3	53.0	68.3	58.4	61.3	61.8	47.2	55.6	54.0	67.3	51.2	48.7	75.7	60.2	39.0	56.8		50.4	54.5	65.2	48.5				
	ビニール、皮革、ゴム、合成材	〃	17.0	29.2	24.0	11.2	29.3	13.4	23.2	16.8	19.9	42.7	23.7	15.2	25.5	28.5	18.1	12.5	16.2	28.3	11.9		17.9	24.7	14.8	24.4				
	木、竹、わら類	〃	7.1	0.4	7.5	6.6	1.4	4.6	3.6	2.1	8.2	3.3	10.5	8.3	3.9	2.9	5.0	2.0	3.7	1.4	1.0		2.9	11.6	6.5	6.4				
	ちゅう芥類	〃	3.4	10.2	5.2	11.5	11.6	13.3	13.0	16.6	6.7	5.0	6.5	8.2	2.6	16.1	20.4	8.0	19.3	21.4	27.3		22.6	6.2	9.1	17.8				
	不燃物類	〃	1.1	3.6	0.5	1.5	0.9	0.4	1.3	2.1	2.4	0.4	2.6	7.3	0.0	0.8	5.3	1.7	0.2	8.3	2.6		1.7	1.7	0.4	0.1				
その他			〃	6.1	1.5	3.8	2.9	3.8	0.0	0.5	1.1	1.0	1.4	1.1	7.0	0.7	0.5	2.5	0.1	0.4	1.6	0.4		4.5	1.3	4.0	2.8			
単位容積重量			kg/m3	120	110	110	100	110	130	130	170	130	130	140	130	110	160	150	170	110	150	180		140	160	150	190			
三ごみ成分の	水分	%	40.7	39.7	38.5	39.5	36.8	20.0	43.8	41.8	46.4	33.2	39.9	46.7	25.1	48.6	46.5	44.3	52.3	55.4	41.7		50.6	41.6	50.6	49.4				
	灰分	〃	5.2	6.9	5.1	7.0	5.2	7.2	4.4	4.9	6.1	5.9	7.8	10.4	7.0	3.5	6.4	5.0	4.6	8.3	9.5		7.1	5.1	4.7	3.9				
	可燃分	〃	54.1	53.4	56.4	53.5	58.0	72.8	51.8	53.3	47.5	60.9	52.3	42.9	67.9	47.9	47.1	50.7	43.1	36.3	48.8		42.3	53.3	44.7	46.7				
	低位発熱量(計算値)	kJ/kg	9,170	9,060	9,660	9,080	10,000	13,200	8,660	8,990	7,780	10,600	8,850	6,910	12,200	7,800	7,700	8,440	6,800	5,450	8,140		6,690	8,990	7,150	7,560				
低位発熱量(実測値)			〃	9,710	11,300	11,200	9,270	14,900	11,300	9,990	10,100	9,690	14,700	10,700	7,230	14,400	10,200	7,550	8,830	5,610	7,230	7,720		7,270	8,630	5,840	8,920			
			【平均】								【平均】								【平均】								【平均】			
ごみの種類組	紙類	%	61.4							60.3				54.7				60.7			52.0				54.7					
	ビニール、皮革、ゴム、合成材	〃	20.4							20.7				25.4				21.1			14.1				21.1					
	木、竹、わら類	〃	5.4							2.9				7.6				3.4			2.4				3.4					
	ちゅう芥類	〃	7.6							13.6				6.6				11.8			23.3				13.9					
	不燃物類	〃	1.7							1.2				3.2				2.0			1.4				1.0					
その他			〃	3.6						1.4				2.6				1.0			0.4				3.2					
単位容積重量			kg/m3	110						135.0				132.5				147.5			145.0				160.0					
三ごみ成分の	水分	%	39.6							35.6				41.6				41.1			47.0				48.1					
	灰分	〃	6.1							5.4				7.6				5.5			7.1				5.2					
	可燃分	〃	54.4							59.0				50.9				53.4			46.0				46.8					
	低位発熱量(計算値)	kJ/kg	9,243							10,212.5				8,535.0				9,035.0			7,470.0				7,597.5					
低位発熱量(実測値)			〃	10,370						11,572.5				10,580.0				10,245.0			6,665.0				7,665.0					
摘 要							摘 要								摘 要								摘 要							

			令和6年度(2024)					
採取年月日			2024/5/27	2024/8/23	2024/11/25	2025/2/14		
証明年月日			2024/6/17	2024/9/19	2024/12/24	2025/3/14		
天候			晴	晴	晴	晴		
気温			単位	°C	23.5	31.0	4.0	5.5
ごみの種類組	紙類、布類	%	41.4	56.6	49.4	53.2		
	ビニール、皮革、ゴム、合成材	〃	12.8	15.6	16.4	29.0		
	木、竹、わら類	〃	2.4	3.8	5.0	1.8		
	ちゅう芥類	〃	41.8	21.8	17.8	7.9		
	不燃物類	〃	0.7	0.4	6.8	6.4		
その他		〃	0.9	1.8	4.6	1.7		
単位容積重量			kg/m3	160	150	140	150	
三ごみ成分の	水分	%	55.0	49.6	42.3	47.5		
	灰分	〃	5.1	3.3	8.0	7.7		
	可燃分	〃	39.9	47.1	49.7	44.8		
	低位発熱量(計算値)	kJ/kg	6,130	7,620	8,300	7,250		
低位発熱量(実測値)			〃	7,060	8,770	9,040	8,580	
			【平均】					
ごみの種類組	紙類	%	50.2					
	ビニール、皮革、ゴム、合成材	〃	18.5					
	木、竹、わら類	〃	3.3					
	ちゅう芥類	〃	22.3					
	不燃物類	〃	3.6					
その他		〃	2.3					
単位容積重量			kg/m3	150				
三ごみ成分の	水分	%	48.6					
	灰分	〃	6.0					
	可燃分	〃	45.4					
	低位発熱量(計算値)	kJ/kg	7,325					
低位発熱量(実測値)			〃	8,363				
摘 要								